



CLiMATUBE® flex

Flexible insulation with self-adhesive closure system made of rubber

Product properties

- Rubber pipe insulation
- Flexible and easy to bend
- Scope of application: Heating and hot water pipes
- Excellent insulating properties:
thermal conductivity of 0.038 W/mK at 40 °C mean temperature
- Heating energy losses reduced by up to ca. 76%
- Fire class: B₁s3d0 (flame resistant)
- Suitable for pipe temperatures from -30 °C to +85 °C



NMC (uk) Ltd.

Tafarnaubach Industrial Estate · UK - NP22 3AA Tredegar, South Wales

Phone: +44 1495 713266

Email: enquiries@nmc-uk.com

www.nmc-climatube.com



Product range

Type	A mm	B mm	Length	Packaging unit
12-9	12 +1/+4	9	1 m	100m
15-9	15 +1/+4	9	1 m	70m
18-9	19 +1/+4	9	1 m	70m
22-9	22 +1/+4	9	1 m	55m
28-9	28 +1/+4	9	1 m	50m
35-9	35 +1/+4	9	1 m	40m
12-13	12 +1/+4	13	1 m	65m
15-13	15 +1/+4	13	1 m	55m
18-13	18 +1/+4	13	1 m	50m
22-13	22 +1/+4	13	1 m	45m
28-13	28 +1/+4	13	1 m	40m
35-13	35 +1/+4	13	1 m	30m